

# ZEOLITE ZeAl 25

**ZEOLITES ZeAL-25** have a unique structural characteristics, high Si/Al ratio and high thermal and chemical stability of this material make it irreplaceable for a number of chemical and industrial processes.

## TECHNICAL DATA

Properties	Chemical and Physical Characteristics		
	unit	Typical Value	Guarantee Value
LOI (1000° C, 1h)	%	8	12 max
Molar ratio SiO <sub>2</sub> /Al <sub>2</sub> O <sub>3</sub>		25	20-30
Water Adsorption Capacity (50% relative humidity, 20° C)	%	2	8 max
D50	µm	2	1 – 5
Na	%	2	1 – 3,5
Crystallinity XRD	%	100	95 min

*The above values have been determined by the measuring methods and instruments of Alumina doo Zvornik.*

## APPLICATIONS

**ZeAL-25** has a significant application in the oil refining and petrochemical industries. It is widely used as a catalyst for hydrocarbon isomerization reactions, such as catalytic cracking and the production of gasoline and diesel fuel. In addition, it is used in medicine, agriculture, etc.

## PACKAGING

We offer different types of packaging depending on your production needs:

Type of packing	Bulk (t)	Big bags (kg)	
Logistic units	Silo truck	Per pallet	Big bags - different types
Mass per logistic unit	25	450, 500	

*Specific type of packaging can be offered on demand*

## LOGISTICS

In order to meet your requirements in terms of delivery, we offer different logistic solutions. Our basic offer in terms of TRANSPORTATION is:

Type of Transportation	Road transportation	Rail transportation
Packaging	In bulk or in bags on pallet.	In bulk or in bags on pallet.

*Other type of delivery on demands.*

